

Requested Patent: WO9844458A1

Title:

METHOD FOR DEFINING ANIMATION PARAMETERS FOR AN ANIMATION
DEFINITION INTERFACE ;

Abstracted Patent: WO9844458 ;

Publication Date: 1998-10-08 ;

Inventor(s): HARATSCH ERICH; OSTERMANN JOERN ;

Applicant(s): AT _T CORP (US) ;

Application Number: WO1998US04308 19980305 ;

Priority Number(s): US19970041732P 19970327 ;

IPC Classification: G06T15/70 ;

Equivalents:

ABSTRACT:


A process is defined for the rapid definition of new animation parameters for proprietary renderers. The process accommodates the peculiarities of proprietary models. In a first step, a proprietary model is animated in a standard modeler and the animated models are saved as VRML files. A converter is used to extract the meaning of a newly defined animation parameter by comparing two or more of the VRML files. Thus, the output of this process is the model and a table describing the new animation parameter. This information is read by the renderer and used whenever the animation parameter is required. The process can easily be used to generate new shapes from the original model.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06T 15/70		A1	(11) International Publication Number: WO 98/44458
			(43) International Publication Date: 8 October 1998 (08.10.98)
(21) International Application Number: PCT/US98/04308		(81) Designated States: CA, JP, MX, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 5 March 1998 (05.03.98)			
(30) Priority Data: 60/041,732 27 March 1997 (27.03.97) US Not furnished 27 February 1998 (27.02.98) US		Published With international search report.	
(71) Applicant: AT & T CORP. [US/US]; 32 Avenue of the Americas, New York, NY 10013-2412 (US).			
(72) Inventors: HARATSCH, Erich; 10 Coventry Square, Holmdel, NJ 07733 (US). OSTERMANN, Joern; 72 Walnut Avenue, Red Bank, NJ 07701 (US).			
(74) Agents: DWORETSKY, Samuel, H. et al.; AT & T Corp., P.O. Box 4110, Middletown, NJ 07748 (US).			

(54) Title: METHOD FOR DEFINING ANIMATION PARAMETERS FOR AN ANIMATION DEFINITION INTERFACE



(57) Abstract

A process is defined for the rapid definition of new animation parameters for proprietary renderers. The process accommodates the peculiarities of proprietary models. In a first step, a proprietary model is animated in a standard modeler and the animated models are saved as VRML files. A converter is used to extract the meaning of a newly defined animation parameter by comparing two or more of the VRML files. Thus, the output of this process is the model and a table describing the new animation parameter. This information is read by the renderer and used whenever the animation parameter is required. The process can easily be used to generate new shapes from the original model.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**METHOD FOR DEFINING ANIMATION
PARAMETERS FOR AN ANIMATION DEFINITION INTERFACE**

This application claims priority to Provisional Application Serial No. 60/041,732 filed March 27, 1997 and entitled "An Animation Definition Interface" and Provisional Application Serial No. 60/042,799 filed April 7, 1997 and entitled "Let Animals And Furniture Speak: Proposal For Extending The Scope OF Face And body Animation."

The present invention generally relates to the field of computer animation and more particularly, is directed to a method for defining animation parameters for an animation definition interface.

BACKGROUND OF THE INVENTION

In recent years, advances in personal computer hardware has made it possible to process audio and digital images on the desktop. These advances were aided by the development of sophisticated formats and standards for coding audio-visual information, such as movies, video, music and the like, in digital compressed formats. Such formats allow large amounts of audio/video data to be processed with relatively low cost equipment.

Under the direction of the International Standards

Organization (ISO) and the International Electro-Technical Commission (IEC), the "Moving Picture Experts Group" ("MPEG") was established to develop the MPEG suite of standards for coding moving pictures and audio. The major advantage of MPEG over other video and audio standards is said to be much smaller file size for the same quality due to the efficient compression techniques employed.

MPEG encoded video files are typically "played" on a PC, Mac or other consumer electronics device using an MPEG video player and MPEG audio files are "played" using an MPEG audio player. Such players are readily available to PC users and the number of MPEG encoded video and audio files is steadily growing.

As the need for more demanding and varied encoding schemes for video and audio content continues to increase, MPEG has been derived into the following categories:

MPEG 1 - Coding of moving pictures
and associated audio for digital
storage media at up to approximately
1.5 Mbit/s;

MPEG 2 - Generic coding of moving
pictures and associated audio

information; and
MPEG 4 - Coding of audio-visual
objects.

Along with the development of MPEG, real-time animation on the desk top also has gained popularity in recent years. Many real-time animation programs, including upcoming MPEG-4 terminals with face and body animation capabilities, can be used to run a proprietary renderer using a proprietary face or body model. Usually, animation of a proprietary model is not compatible with MPEG-4 requirements. Furthermore, the current implementation and modification of animation parameters, like smiles or eyebrow movement, with these renderers is cumbersome and time consuming. Thus, there is a need in the art for an improved method of processing animation parameters.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to obviate the above-noted shortcomings and disadvantages of real-time animation processes known in the prior art.

Another object of the present invention is to provide an animation definition interface for an MPEG renderer which can be easily and inexpensively

implemented allowing for animation of arbitrary downloaded models in the MPEG-4 terminal.

It is another object of the present invention to provide an inexpensive and easily followed method for real-time animation.

The above mentioned disadvantages of prior art real-time animation with MPEG compliant renderers can be eliminated or substantially reduced by the present invention. In accordance with the invention, a method is provided that allows the rapid definition of animation parameters for proprietary models downloaded from an MPEG-4 encoder and their inclusion into proprietary real-time rendering software that might also be MPEG-4 compliant. The proprietary model can be read into any commercially available modeler. The modeler is then used to define the behavior of different animation parameters. For each animation parameter, a modified model is created and stored. Model analysis software, known as an animation definition interface, compares the original model with the animated model and extracts the essential animation parameters which represents the differences between the original and modified models. These parameters are stored in tables and are used by the real-time animation program to generate the desired

expressions.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the present invention are set out with particularity in the appended claims, but the invention will be understood more fully and clearly from the following detailed description of the invention as set forth in the accompanying drawings, in which:

Figures 1 illustrates how the animation definition interface of the present invention is integrated with a modeler and renderer;

Figure 2 illustrates the piece-wise linear approximation of a complex deformation applied to a vertex of the uniform model; and

Figure 3 illustrates the use of MPEG-4 for animation of computer graphics heads by synthetic speech and animation parameters.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The MPEG-4 standard described above strives to define a standardized interface to allow animation of face and body models within an MPEG-4 terminal. Due to the rapid advances in computer graphics hardware, it is not foreseen that MPEG-4 will standardize face and body

models. Instead, face and body definition parameters ("FDP", "BDP") are defined for specifying the shape and surface of a model. For the animation of the models, face and body animation parameters ("FAP", "BAP") are standardized.

These animation parameters include low-level parameters like "move left eyebrow up" and "tongue roll" as well as high-level parameters like "smile". Assuming that different terminals allow for models with different degrees of complexity, a process is required that allows the rapid development of models suited for animation. The use of standardized file format like Virtual Reality Modeling Language ("VRML") allow the use of commonly available modeling software (modelers), like COSMO 3D or PowerAnimator, to design animations. However, formats like VRML 1, VRML 2, and OpenInventor only support the description of rigid objects.

VRML was conceived in the early part of 1994 and was developed in response to a need for a three dimensional graphical visualization standard. VRML 1.0 was the first version of the standard and provided basic support for describing three dimensional objects such as spheres, planes, cubes cylinders, cones and the like.

Version 2.0 of the VRML standard built on the

progress of Version 1.0 by adding such capabilities as object behavior.

Face and body animation requires flexible deformation. Such a feature is not currently conveniently supported by OpenInventor or VRML 2. Accordingly, real-time renders which are designed to read and write VRML or OpenInventor files must be modified in order to accommodate animation. In addition, convenient editors for defining the animation capabilities are not known in the prior art.

In accordance with the present invention, an interface between a modeler, e.g., Alias/Wavefront Power Animator, and real-time animation software is provided. The present invention allows for the rapid definition, modification and implementation of animation parameters.

Since the interface reads VRML files from the modeler, it is independent of the modeler. The interface writes a VRML file and one accompanying table for each defined animation parameter thus making this information easily integrate able into proprietary renderers.

The interface of the invention takes as its input several VRML files describing static models with a topology appropriate for the renderer. Figure 1 illustrated how the system is integrated with the

modeler and the renderer. The model of the renderer is exported as a VRML file and read into the modeler. In order to design the behavior of the model for one animation parameter, the model is deformed using the tools of the modeler. Usually, restrictions on the topology of the model exist. For simplicity, it is assumed that the model is deformed only by moving relevant vertices and not by changing its topology. The modeler exports the deformed model as a VRML file.

The Animation Definition Interface (ADI) compares the output of the modeler with its input, i.e., the model exported from the renderer. By comparing vertex positions of the two models, the vertices affected by the newly designed animation parameter can be identified. The ADI computes for each affected vertex a 3D displacement vector defining the deformation and exports this information in a table.

The renderer reads the VRML file of the model and the table in order to determine the definition of the new animation parameter. The renderer can now use the newly defined animation as required by the animation parameters.

Most of the newly available graphics boards for PCs and workstations support rendering based on the OpenGL

engine. The VRML 2 file format is based on OpenInventor that itself is based on OpenGL. Thus, it is essential to enable real-time deformations of models rendered on an OpenGL engine. Use of a scene graph usually does not allow the movement of parts of an object. Therefore, the vertex positions of the scene graph are updated through the animation parameters as defined in the table. Only the vertex coordinates of the scene graph are updated thus allowing one to take full advantage of the OpenGL rendering engine speed for global motions, lighting texture mapping, etc.

The conversion process described above allows the renderer to only create deformations of moving vertices along the defined 3D displacement vector. While this might be sufficient for simple actions like *move "left eye brow up"*, complex motions like *"smile"* or *"tongue roll up"* can not be sufficiently modeled by linearly moving vertices. Thus, in accordance with the present invention, several VRML files are created for different phases of the animation or values of the animation parameter. Such files allow for a piece-wise linear approximation of complex deformations. This process is illustrated in Figure 2.

The following table shows an example of an

animation parameter ("AP") definition for 2 vertices, where the 3-D motion is defined in 3 intervals. The parameter AP is positive and in Interval 1 is valid for $0 < AP \leq 0.33$, in Interval 2 is valid for $0.33 < AP \leq 0.66$ and in Interval 3 is valid for $0.66 < AP \leq 1.0$.

Vertex No.	1 st Interval	2 nd Interval	3 rd Interval
5	(0.1, 0.7, -5)	(0, 2, 4)	(0, 0.1, -0.1)
13	(3, 4, -2)	(3, 2, 4)	(-1, -2, -3)

Given $AP = 0.3$, vertex 5 would be displaced by:

$$0.3 \times (0.1, 0.7, -5)^T.$$

For $AP = 0.6$, vertex 5 would be displaced by:

$$0.33 \times (0.1, 0.7, -5)^T + (0.6 - 0.33) \times (0, 2, 4)^T.$$

The above approach can be extended in order to allow positive and negative animation parameters as well as unequal intervals for defining the motion of a vertex. Other extensions include replacing the linear approximation of the vertex motion by general functions like polynomials. These functions could be different for each animation parameter. A further generalization is to make these functions dependent on more than one animation parameter.

For a smile, writing three files with "smile=0.3", "smile=0.7" and "smile=1.0" are sufficient to allow for a subjectively pleasant piece-wise linear approximation of this relatively complex deformation.

The above outlined procedure can be used to define the entire set of MPEG-4 FAPs for a proprietary face animation renderer. The model is an extension of Parke's model. Applicants have found that FAPs integrate nicely with the model's talking capability controlled by a TTS system.

Animated sequences using different personalities also are illustrated in Figure 3.

Arbitrary head models in VRML and animation tables can be created in two ways, a natural for personalized head models and a synthetic one.

In the natural approach, a VRML model of a person's head is created by, for example, using cyberscan data. The animation table is generated by image analysis. Images of the person are taken in a neutral state and for each facial expression corresponding to the different animation parameters. The method described above could be used to calculate the displacement vectors for *IndexedFaceSet* nodes. Applying this algorithm for different intensities of the person's

expression improves the realism of the facial movements during animation. An animation system which downloads a person's data obtained in this way represents a new architecture for a primitive model-based decoder.

An example of how the present invention may be implemented will now be described.

ASCII Specification - FDP					
000	000	exposedField	SFNode	featurePointsCoord	NULL
001	001	exposedField	SFNode	textureCoord4Feature Points	NULL
010	010	exposedField	SFNode	calibrationMesh	NULL
011	011	exposedField	SFNode	faceTexture	NULL
100	100	exposedField	MFNode	animationDefinitionTables[]	NULL
101	101	exposedField	SFNode	faceSceneGraph	NULL

The FDP node defines the face model to be used at the receiver. Two options can be supported:

1. calibration information is downloaded, so that the proprietary face of the receiver can be configured using facial feature points and optionally a 3D mesh or texture; and
- 2 a face model is downloaded with the animation

definition of the Facial Animation Parameters.

This face model replaces the proprietary face model in the receiver.

Each field may be described as follows:

featurePointsCoord	contains a Coordinate node. Specifies feature points for the calibration of the proprietary face. The coordinates are listed in the "point" field in the Coordinate node in the prescribed order, that a feature point with a lower label is listed before a feature point with a higher label (e.g. feature point 3.14 before feature point 4.1).
textureCoord4- Feature Points	contains a TextureCoordinate node. Specifies the texture coordinates for the feature points.
calibrationMesh	contains an IndexedFaceSet node. Specifies a 3D mesh for the calibration of the proprietary face model. All fields in the IndexedFaceSet node can be used as calibration information.
faceTexture	contains an ImageTexture or PixelTexture node. Specifies texture to be applied on the proprietary face model.
animationDefinition tables	contains AnimationDefinitionTable nodes. If a face model is downloaded, the behavior of FAPs is defined in this field.
faceSceneGraph	contains a Group node. Grouping node for face model rendered in the compositor. Can also be used to download a face model: in this case the effect of Facial Animation Parameters is defined in the

"animationDefinitionTables" field.

Other ASCII specifications are set forth in the tables below:

??		AnimationDefinitionTable				
00	field	SFInt	fapID	1	1	68
01	field	SFInt	highLevelSelect	1	1	64
10	0 exposedfield	Mfnode	table []	NULL		

??		AnimationDefTransform			
00	field	??	nodeIDTransform	" "	
01	field	SFString	fieldID	na	
10	field	GenericSF	fieldValue	na	

??		AnimationDefIndexedFaceSet			
00	field	??	nodeIDIndexedFaceSet		
01	field	MFInt32	intervalBorders []		
10	field	MFInt32	coordIndex []		
11	field	MFVec3f	displacements []		

While the present invention has been described with respect to a preferred embodiment, the invention is not limited thereto. In general, this version is applicable when defining animation parameters defining flexible deformation of computer graphic models. The scope of the invention is limited only by the attached claims.

CLAIMS

1. A method for defining a set of computer animation parameters for an object to be animated electronically, wherein said animation is achieved by electronically altering at least a portion of said object in a controlled manner, said method comprising the steps of:
 - obtaining an electronic reference model of said object to be animated;
 - altering said reference model to form a modified model corresponding to a first animation parameter;
 - determining the physical differences between said reference model and said modified model and storing said differences as said first animation parameter;
 - repeating said altering and said determining steps for each of said animation parameters to be defined; and
 - providing said stored parameters to a rendering device for generation of said animation in accordance with said stored parameters.
2. The method of claim 1 further including the definition of an object as a scenegraph and the definition of high level animation parameters to allow rigid and flexible deformation.
3. The method of claim 1 further including the step of

defining a major animation parameter, said step includes the sub-steps of:

defining a plurality of associated animation parameters representing an animation sequence; and
storing said plurality of associated animation parameters as said major parameter.

4. The method of claim 1, wherein said object includes characteristics of a human being and said method further includes the step of defining a major animation parameter representing a human expression, said step includes the sub-steps of:

defining a plurality of animation parameters representing said human expression; and
storing said plurality of animation parameters as said major parameter.

5. The method of claim 1, wherein said animation is described by spline functions.

6. The method of claim 1, wherein said animation is described by rational polynomial functions.

7. The method of claim 1, wherein said animation is described by general functions.

8. The method of claim 1, wherein said determining step includes the sub-step of comparing the vertex positions of said modified model to the vertex positions of said

reference model.

9. The method of claim 1, wherein said determining step includes the step of approximating the differences between said reference model and said modified model and storing said differences as said first animation parameters.

1/1

FIG. 1




FIG. 2





FIG. 3



INTERNATIONAL SEARCH REPORT

National Application No
PCT/US 98/04308

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G06T15/70

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	LI-AN TANG ET AL: "ANALYSIS-BASED FACIAL EXPRESSION SYNTHESIS" PROCEEDINGS OF THE INTERNATIONAL CONFERENCE ON IMAGE PROCESSING (IC, AUSTIN, NOV. 13 - 16, 1994, vol. VOL. 3, no. CONF. 1, 13 November 1994, INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS, pages 98-102, XP000522790 see page 99, left-hand column, paragraph 2 --- -/--	1-4

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

8 July 1998

Date of mailing of the international search report

21/07/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Perez Molina, E

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/04308

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	TAKAAKI AKIMOTO ET AL: "3D FACIAL MODEL CREATION USING GENERIC MODEL AND FRONT AND SIDE VIEWS OF FACE" IEICE TRANSACTIONS ON INFORMATION AND SYSTEMS, vol. E75 - D, no. 2, 1 March 1992, pages 191-197, XP000301166 see page 194, left-hand column, paragraph 4; figure 1	1
X	CHOI C S ET AL: "ANALYSIS AND SYNTHESIS OF FACIAL IMAGE SEQUENCES IN MODEL-BASED IMAGE CODING" IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS FOR VIDEO TECHNOLOGY, vol. 4, no. 3, 1 June 1994, pages 257-275, XP000460758 see page 258, paragraph II	1
P,A	HARATSCH E ET AL: "Parameter-based animation of arbitrary 3D head models" PICTURE CODING SYMPOSIUM. PCS 97, BERLIN, GERMANY, 10-12 SEPT. 1997, no. 143, ISSN 0341-0196, ITG-FACHBERICHTE, 1997, VDE-VERLAG, GERMANY, pages 81-84, XP002070808 see page 81, paragraph 3	1
P,A	WO 98 06069 A (INTERVAL RESEARCH CORP) 12 February 1998 see claim 1	1,3
P,A	DOENGES P K ET AL: "Audio/video and synthetic graphics/audio for mixed media" SIGNAL PROCESSING. IMAGE COMMUNICATION, vol. 9, no. 4, May 1997, page 433-463 XP004075338 see page 449, paragraph 5	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/04308

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9806069 A	12-02-1998	AU 3811197 A	25-02-1998